



## Premier-Plenum Duct

Premier Plenum Duct is a flexible, non-metallic, corrugated raceway used for effective cable and fiber optic management within interior raceways. Premier Plenum meets UL-(910) standards for the National Electrical Code, Article 770, and satisfies UL-2024 standards for low smoke and flame propagation.

Premier Plenum is offered in 1", 1¼" and 1½", with pre-installed pull tape for easy cable installation. The standard color is orange and is offered in a variety of other colors. Sequential marked footage is standard. Custom options, such as multiple colors per reel and Slit Duct, are also available.

Future growth or maintenance of your interior cable system is made easy with Premier Plenum.



### Plenum Reels

Size	Color	Part No.	Nominal I.D.	Nominal O.D.	Pull Tape	Reel Size	Reel Length (ft.)
1"	Orange	P-100T- 500	1.049"	1.35"	900 lb	36-36-21	500
1"	Orange	P-100T-1000	1.049"	1.35"	900 lb	36-36-21	1000
1"	Orange	P-100T-2000	1.049"	1.35"	900 lb	44-36-21	2000
1"	Orange	P-100T-2800	1.049"	1.35"	900 lb	48-41-24	2800
1"	Orange	P-100T-5000	1.049"	1.35"	900 lb	66-41-24	5000
1"	Orange	P-100T-6000	1.049"	1.35"	900 lb	72-41-24	6000
1"	Orange	P-100T-9000	1.049"	1.35"	900 lb	82-41-24	9000
1¼"	Orange	P-125T- 700	1.25"	1.56"	900 lb	36-36-21	700
1¼"	Orange	P-125T-1500	1.25"	1.56"	900 lb	44-36-21	1500
1¼"	Orange	P-125T-1800	1.25"	1.56"	900 lb	48-41-24	1800
1¼"	Orange	P-125T-3400	1.25"	1.56"	900 lb	66-41-24	3400
1¼"	Orange	P-125T-4000	1.25"	1.56"	900 lb	72-41-24	4000
1¼"	Orange	P-125T-6000	1.25"	1.56"	900 lb	82-41-24	6000
1½"	Orange	P-150T- 500	1.57"	1.80"	900 lb	36-36-21	500
1½"	Orange	P-150T- 700	1.57"	1.80"	900 lb	44-36-21	700
1½"	Orange	P-150T-1000	1.57"	1.80"	900 lb	48-41-24	1000
1½"	Orange	P-150T-2500	1.57"	1.80"	900 lb	66-41-24	2500
1½"	Orange	P-150T-3500	1.57"	1.80"	900 lb	72-41-24	3500
1½"	Orange	P-150T-5000	1.57"	1.80"	900 lb	82-41-24	5000



### Plenum Coils

Size	Color	Part No.	Nominal I.D.	Nominal O.D.	Pull Tape	Coil Length (ft.)
1"	Orange	P-100T-500	1.049"	1.35"	900 lb	Up to 500
1¼"	Orange	P-125T-500	1.25"	1.56"	900 lb	Up to 500
1½"	Orange	P-150T-350	1.57"	1.80"	900 lb	Up to 350

### Test Results (Using Test Method UL-2024)

Properties	Value
Smoke peak optical	0.02
Smoke average optical density	0.01
Max. flame spread distance (ft.)	1.5'
Max. flame temperature	554°F

### Sample Part Number

P	100	T	S	2500
Plenum	1" (I.D.)	Polyester Tape	*Slit Duct (optional)	Put-Up

\* Pull tape not available w/ Slit Duct