

## Corrugated HDPE

Premier Corrugated HDPE is manufactured from High Density Polyethylene (HDPE) and is intended to be placed inside of existing innerduct. It's ideal for pulls under 1000 ft. and is designed to reduce surface contact when pulling cable. This lightweight product offers maximum flexibility, and allows for installation in small or restricted areas. Corrugated duct is available in 3/4", 1", 1 1/4", 1 1/2" and 2". The standard color is orange and is offered in a variety of other colors. Sequential marked footage is standard. Custom options, such as multiple colors per reel and Slit Duct, are also available.



### Corrugated HDPE Reels

Size	Color	Part No.	Nominal I.D.	Nominal O.D.	Pull Tape	Reel Size	Reel Length (ft.)
3/4"	Orange	PEC-075T- 2200	0.932"	1.00"	1130 lb	36-38-36	2200
3/4"	Orange	PEC-075T- 6300	0.932"	1.00"	1130 lb	48-45-48	6300
3/4"	Orange	PEC-075T- 9600	0.932"	1.00"	1130 lb	66-45-66	9600
3/4"	Orange	PEC-075T-11500	0.932"	1.00"	1130 lb	72-45-72	11500
3/4"	Orange	PEC-075T-15500	0.932"	1.00"	1130 lb	82-45-82	15500
1"	Orange	PEC-100T- 500	1.049"	1.35"	1130 lb	36-36-21	500
1"	Orange	PEC-100T-1200	1.049"	1.35"	1130 lb	36-36-21	1200
1"	Orange	PEC-100T-2800	1.049"	1.35"	1130 lb	48-41-24	2800
1"	Orange	PEC-100T-5000	1.049"	1.35"	1130 lb	66-41-24	5000
1"	Orange	PEC-100T-6000	1.049"	1.35"	1130 lb	72-41-24	6000
1"	Orange	PEC-100T-9000	1.049"	1.35"	1130 lb	82-41-24	9000
1 1/4"	Orange	PEC-125T- 700	1.25"	1.56"	1130 lb	36-36-21	700
1 1/4"	Orange	PEC-125T-1500	1.25"	1.56"	1130 lb	48-41-24	1800
1 1/4"	Orange	PEC-125T-3400	1.25"	1.56"	1130 lb	66-41-24	3400
1 1/4"	Orange	PEC-125T-4000	1.25"	1.56"	1130 lb	72-41-24	4000
1 1/4"	Orange	PEC-125T-6200	1.25"	1.56"	1130 lb	82-41-24	6200
1 1/2"	Orange	PEC-150T- 550	1.57"	1.80"	1130 lb	36-36-21	550
1 1/2"	Orange	PEC-150T-1000	1.57"	1.80"	1130 lb	48-41-24	1200
1 1/2"	Orange	PEC-150T-2500	1.57"	1.80"	1130 lb	66-41-24	2500
1 1/2"	Orange	PEC-150T-3500	1.57"	1.80"	1130 lb	72-41-24	3500
1 1/2"	Orange	PEC-150T-4500	1.57"	1.80"	1130 lb	82-41-24	4500
2"	Orange	PEC-200T- 300	2.0"	2.349"	1130 lb	36-41-24	300
2"	Orange	PEC-200T- 700	2.0"	2.349"	1130 lb	48-41-24	700
2"	Orange	PEC-200T-1600	2.0"	2.349"	1130 lb	66-41-24	1600
2"	Orange	PEC-200T-2000	2.0"	2.349"	1130 lb	72-41-24	2000
2"	Orange	PEC-200T-2800	2.0"	2.349"	1130 lb	82-41-24	2800

### Corrugated HDPE Coils

Size	Color	Part No.	Nominal I.D.	Nominal O.D.	Pull Tape	Coil Length (ft.)
3/4"	Orange	PEC-075T-1050	0.932"	1.00"	1130 lb	Up to 1050
1"	Orange	PEC-100T- 500	1.049"	1.35"	1130 lb	Up to 500
1 1/4"	Orange	PEC-125T- 500	1.25"	1.56"	1130 lb	Up to 500
1 1/2"	Orange	PEC-150T- 350	1.57"	1.80"	1130 lb	Up to 350
2"	Orange	PEC-200	2.0"	2.349"	1130 lb	Up to 250

#### Sample Part Number

PE	C	100	T	S	2500
Polyethylene (High Density)	Corrugated	1" (I.D.)	Polyester Tape	*Slit Duct (optional)	Put-Up

\* Pull tape not available w/ Slit Duct

**Note:** Corrugated products are not recommended for direct bury due to lack of crush resistance. For direct bury the industry's recommendation is smoothwall products.